


A large digital display on a trailer showing license plate numbers in red. The display is mounted on a black frame with a solar panel on top.

ALPR MESSAGE TRAILER

VETTED'S ALPR MESSAGE TRAILER PROVIDES INFORMATION TO MOTORISTS WHILE CAPTURING REAL-TIME VEHICLE INTELLIGENCE.

Combine the power of automated license plate recognition (ALPR) with a configurable messaging display with Vetted's ALPR Message Trailer systems.

Available in three configurations, these systems are designed to be deployed by a single officer. With digital touchscreen controls, remote message changing capabilities, and solar recharging battery power, your ALPR trailer system is ready to serve on short and long-term missions.



Portable and Easy to Deploy

Vetted's ALPR Message Trailers are designed for any situation that may arise. Built with rapid, effortless deployment in mind these compact and lightweight trailers are easy to tow and utilize a simple winch system to accommodate a single-person setup scenario.




Operational Runtime

Ready to serve you well day in and day out, the Vetted ALPR Message Trailers come with a selection of power supplies and a range of runtimes and solar options, perfect for creating the ideal setup.



DOT-Compliant

Designed for ease of use Vetted's ALPR Message Trailers are DOT-compliant, roadside ready and employ a continuous welded steel frame design and aircraft-grade powder coat finish to withstand the elements and an array of safety features. Both the battery box and ALPR controls are enclosed in separate, vented, and locked cabinets to improve safety and performance.

	ALPR MESSAGE TRAILERS		
	STANDARD	XL	XL + PTZ
Part #	VSS-STD-MSG-VLT	VSS-XL-MSG-VLT	VSS-XL-MSG-VLT-PTZ
Highlighted Features	<ul style="list-style-type: none"> • 365W solar panel • 71" x 48" message display board • Manual Winch system to raise or lower the message board 	<ul style="list-style-type: none"> • 555W tilting solar array • 96" x 55" message display board • Hydraulic cylinder mast to raise or lower the message board 	<ul style="list-style-type: none"> • 470W tilting solar array • 96" x 55" message display board • Hydraulic cylinder mast to raise and lower the message board • Electric telescopic mast for single PTZ (camera purchased separately)
Power System	<ul style="list-style-type: none"> • 24V system • 4 x 12V 200Ah AGM batteries • 7-10 day estimated runtime (dependent on geographic location and sunlight) 	<ul style="list-style-type: none"> • 12V system • 3x 12V 200Ah AGM batteries • 7-10 day estimated runtime (dependent on geographic location and sunlight) 	<ul style="list-style-type: none"> • 12V system • 3x 12V 200Ah AGM batteries • 5-7 day estimated runtime (dependent on geographic location and sunlight)
	• Multi-staged smart battery charger		• 120VAC recharging system
ALPR	• Two (2) Vigilant L5F ALPR cameras	• LEARN ALPR monitoring software	• Vigilant VLT tablet, Windows OS, 250 GB, & collapsible keyboard
Radar	FCC compliant approach-only K-band radar		
Messaging	<ul style="list-style-type: none"> • Touchscreen controller for easy message programming • Preprogrammed messages and bold arrow patterns 	<ul style="list-style-type: none"> • Remote sign display management capabilities • Multi-level security, restricts access to control messaging 	• Internal clock facilitates built-in schedule programming
Connectivity	• 4G/5G cellular modem* (FirstNet® Ready)		• Onboard GPS
Design	<ul style="list-style-type: none"> • All weather operation • Removable drawbar for added theft protection 	<ul style="list-style-type: none"> • Secured powder coated (white) aluminum battery box and equipment enclosure 	<ul style="list-style-type: none"> • Tower rotates 360° for optimal positioning • DOT-approved trailer body

* Requires customer-provided cellular service plan; FirstNet is a registered trademark and service mark of the First Responder Network Authority. All other marks are the property of their respective owners.



VSS-STD-MSG-VLT**



VSS-XL-MSG-VLT**



VSS-XL-MSG-VLT-PTZ**

** Images provided for visual reference. Actual products may vary

CONTACT US TODAY

727.440.3245

sales@vettedsecuritysolutions.com

VETTEDSECURITYSOLUTIONS.COM



© 2022 Vetted Security Solutions. All Rights Reserved. Revised 02.2023

ALPR MESSAGE TRAILER OPTIONS

TRAILER ENHANCEMENTS

Trailer Type	STANDARD	XL	XL + PTZ
Vetted L5F Trailer Camera Security Enclosure (white)		VSS-L5F-ENC (requires 2 per trailer)	
Vetted Virtual Technician (VVT) Annual Software License (single trailer)		VSS-TRL-VVT-1	

REQUIRED SOFTWARE & SERVICES

Vigilant CLK Annual Software License (priced per camera per year*) *Requires new/existing Vigilant Enterprise Service Agreement (ESA)	1-14 total camera units VSBSCSVC-01
	15-30 total camera units VSBSCSVC-02
	31-60 total camera units VSBSCSVC-03
	Over 60 total camera units VSBSCSVC-04
Vigilant Solutions Start Up and Commissioning	SSUPSYS-COM
Trailer Shipping (per trailer)	VSS-SHIP-TRLR

NEW VIGILANT ACCOUNT REQUIRED SOFTWARE & SERVICES

Vigilant Startup of a New LEARN Account	SSUPLN-COM
Vigilant Training	VSPTRNG
Vigilant Certified Partner Travel	VSPTRVL-01

OPTIONAL SOFTWARE

Avigilon Single Channel Enterprise VMS License (1 license per trailer)	ACC7-ENT
Vigilant LinC Licensing Add On for PTZ Camera (1 license per camera)	3PC-ISL

CONTACT US TODAY

727.440.3245




sales@vettedsecuritysolutions.com

VETTEDSECURITYSOLUTIONS.COM






© 2022 Vetted Security Solutions. All Rights Reserved. Revised 02.2023

AXIS PTZ CAMERA OPTIONS (1 PER XL+PTZ)

			
Model #	Q6135-LE	Q6315-LE	Q6075-E
Part #	01959-004	01925-004	01752-004
Imaging	2 MP with 32X optical zoom	2 MP with 31X optical zoom	2 MP 40X optical zoom
Power	60Hz, Axis High PoE midspan 1-port: 100–240V AC, max 74W Camera consumption: typical 13.5W (no IR), max 51W Axis PoE+ midspan 1-port: 100–240V AC, max 37W IEEE 802.3at Type 2 Class 4 Camera consumption: typical 13.5W, max 25W	Axis High PoE 60W SFP midspan 1-port: 100–240V AC, max 1.5 A IEEE802.3bt Type 3 Class 6 Camera consumption: typical 17W (no IR), max 51W	60Hz, Axis High PoE 60W SFP midspan: 100–240 V AC, max 66.1W Camera consumption: typical 14W, max 51W
IR Illumination	OptimizedIR		-
Trailer Mounting Accessories	Pendant Kit 5502-431		
Onboard Storage (contact sales)	Support for microSD/microSDHC/microSDXC card		

AVIGILON PTZ CAMERA OPTIONS (1 PER XL+PTZ)

			
Part #	2.0C-H5A-PTZ-DP36	4.0C-H5A-PTZ-DP36	8.0C-H5A-PTZ-DP36
Imaging	2 MP with 30X optical zoom	4 MP with 36X optical zoom	8 MP with 36X optical zoom
Power	51W max with 24 VDC aux power, 75 VA with 24 VAC aux power, 51W max with 60W PoE++, 25.5W max with 30W PoE+		
IR Illumination	-		
Trailer Mounting Accessories	NPT Pendant Adapter IRPTZ-MNT-NPTAI		
Onboard Storage (contact sales)	2x microSD/microSDHC/microSDXC card slot - video speed class card required Class V 30 or better recommended		

CONTACT US TODAY

727.440.3245

sales@vettedsecuritysolutions.com

VETTEDSECURITYSOLUTIONS.COM



© 2022 Vetted Security Solutions. All Rights Reserved. Revised 02.2023

STORAGE UPGRADE OPTIONS (1 PER XL+PTZ)

1 TB M.2 NVMe SSD	VSS-VLT-SSD-M2-1TB
2 TB M.2 NVMe SSD	VSS-VLT-SSD-M2-2TB
4 TB M.2 NVMe SSD	VSS-VLT-SSD-M2-4TB

WARRANTY OPTIONS

2-Camera Mobile LPR System- Extended Hardware Warranty	1 Year Warranty CDMS21HWW
	2 & 3 Year Warranty CDMS22HWW
	2-4 Year Warranty CDMS23HWW
	2-5 Year Warranty CDMS24HWW

CONTACT US TODAY

727.440.3245

sales@vettedsecuritysolutions.com

VETTEDSECURITYSOLUTIONS.COM



© 2022 Vetted Security Solutions. All Rights Reserved. Revised 02.2023